



- ▶ Residential / Industrial luminaire
- ▶ Diffused light with IP65/IP66
- ▶ Traditional look with LED tech inside
- ▶ Short ROI (Return of Investment)
- ▶ Optional Dimming/Emergency/Corridor

Benefits

- Moisture-proof luminaire IP65/IP66s
- Excellent total cost of ownership with attractive payback times
- Long-life LEDs reduce the maintenance and product replacement costs
- Unified Glare Rating is lower or equal to fluorescent tube(UGR<19)
- Three standards available - 600 mm / 1200 mm / 1500 mm
- No annoying noises, vibrations and low flickering
- Significant sustainability due to lower energy, reduced waste and no hazardous substances such as mercury and lead
- 100% efficacy - directed light which guarantees that all the luminosity goes where is needed
- Approved for indoor use or in canopied outdoor areas

ProLight is a highly functional luminaire range that delivers great lighting quality in the face of dust, dirt and moisture. Durable, maintenance free and efficient: high-quality LED luminaires are a reliable lighting tool for keeping operating costs sustainably low. Aspects of economy have been combined with classical styling, performance and toughness for ProLight. When it comes to lighting quality, ProLight is bound to impress with excellent colour rendering up to Ra > 90 and colour temperatures from 2700 Kelvin to 6500 K. With a service life of 50,000 hours at 80 % luminous flux, ProLight is virtually maintenance free. Optionally ProLight could implement corridor function to increase the energy saving to maximum. According to the latest standards ProLight can be equipped with Emergency module with up to 4 hours stand alone time. The dimming option can also help to reduce the electricity bill. All these options make ProLight the perfect solution for even the most rigorous project.

| MODEL | ProLight 60 | ProLight 120 | ProLight 150 |
|-----------------------------|---|--------------|--------------|
| Input power | 20 W | 40 W | 50 W |
| Useful quantity of light | 2 400 Lm | 4 800 Lm | 6 000 Lm |
| UGR | UGR 19 | | |
| Led used / pcs | Osram/Samsung | | |
| Power supply / Pfc | 230V AC/ PFC>90 | | |
| Internal thermal protection | automatic | | |
| Working temperature | -25° to +40°C | | |
| Environment protection | IP 65/ Optional IP 67 | | |
| Dimensions mm | 600x110x100 | 1200x110x100 | 1500x110x100 |
| Weight kg | 2 kg | 2.3 kg | 2.6 kg |
| LED Lm70 | 50.000 h | | |
| Application | Working halls, shops, Malls, underground parkings | | |

